

THREE FINGER CLIPS (METRIC)



PART NUMBER (Code)	OUTSIDE DIAMETER	OVERALL LENGTH	OPERATING RANGE PIN DIA.	TEST PIN DIAMETER	MAXIMUM INSERTION FORCE	MINIMUM WITHDRAWAL FORCE
YT-1* (310)	.787	1.905	.381 - .508	.432	80 GM	15 GM
YT-1L* (311)	.787	1.905	.381 - .533	.457	90 GM	14 GM
YT-2 (320)	.813	1.270	.381 - .457	.432	400 GM	100 GM
YT-3 (330)	.787	1.905	.381 - .508	.432	42 GM	14 GM
YT-3X (331)	.787	1.905	.381 - .533	.457	30 GM	10 GM
YT-4 (340)	.5969	1.651	.178 - .330	.279	30 GM	9 GM
YT-5 (350)	.4978	1.346	.152 - .279	.203	30 GM	10 GM

*-SIZING PIN DIAMETER IS .533.

NOTE: ALL CLIPS PRODUCED FROM BeCu ALLOY 172 1/2 HD AND HEAT TREATED AFTER FORMING.
ALL SPECIFICATIONS REFER TO CLIPS THAT ARE NOT PLATED.

THE ABOVE INFORMATION IS PROVIDED FOR REFERENCE ONLY. ENGINEERING DRAWINGS CAN BE PROVIDED.

YTCO TECHNOLOGY CO.,LTD.

3/F, ZhongYuGuan Industrial Park A2 Building, LongHua New District, ShenZhen, China

TELEPHONE: +86 (755) 6196-1091

+86 (755) 6196-1092

FAX: +86 (755) 6196-1093

www.ytco.co

TECHNICAL PRODUCT DATA-REV. 22, 12/10/12